

**Amendments to and Listing of the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-13. (Withdrawn)

14. (Currently Amended) A method for positioning a prosthetic acetabulum with inner and outer surfaces in an anatomical or prosthetic cavity of a patient's hip, comprising the steps of:

providing a tool having a handle for manipulating the acetabulum, the handle, including a rod and a head, the head adapted to cooperatively engage ~~an~~ inner faces of an elastically deformable ring including a plurality of petals in of an endpiece that is used to grip the inner surface ~~an internal surface~~ of the acetabulum and which endpiece is removably secured to the distal end of the handle, the petals of the elastically deformable ring including ~~an~~ outer surfaces adapted to wedge against the ~~an~~ inner surface of the acetabulum and ~~an~~ opposite inner surfaces adapted to interact said endpiece with said handle, and wherein said handle further includes elements for applying a first force to urge said head into cooperative engagement with said inner surfaces of said petals of the elastically deformable ring to thereby radially expand said petals of the elastically deformable ring with respect to a longitudinal axis of said endpiece[,];

placing said endpiece in engagement with said head of said handle and said head within said acetabulum and providing a first force between said head and said endpiece so as to provoke radial elastic deformation of the petals of said elastically deformable ring to thereby grip said acetabulum by said endpiece[,];

positioning said acetabulum in said cavity of said patient's hip[,];

applying a second force along said handle to cause said acetabulum to seat within said cavity of said patient's hip[,];

disengaging said head from said endpiece and releasing said first force to allow the petals of said elastically deformable ring to recover to a non-expanded configuration[,]; and withdrawing said endpiece from the positioned acetabulum.

15. (Previously Presented) The method of claim 14 including the additional steps of:  
providing a plurality of endpieces having different sizes, different geometric configurations, or both;  
selecting an endpiece from said plurality of endpieces that closely matches said inner surface of said acetabulum and securing said selected endpiece to said distal end of said handle.
16. (Previously Presented) The method of claim 14, wherein the elements for applying the first force to the head include a threaded portion on the rod, a grip screwed on the threaded section and a movable sleeve fitted between the grip and the head so that the head is positioned on the rod by rotating the grip on the threaded portion of the rod to move the sleeve to different positions on the rod.
17. (Previously Presented) The method of claim 16, wherein the first force is applied by rotating the grip to move the sleeve toward the endpiece secured to the tool.
18. (Previously Presented) The method of claim 14, wherein the endpiece includes a supple part and a rigid part secured to the supple part, wherein the rigid part includes structure for removably securing the rod to the endpiece.
19. (Previously Presented) The method of claim 18 wherein the rigid part of the endpiece includes a tapped section adapted to be secured to a threaded section on a distal end of the rod.
20. (Previously Presented) The method of claim 19 wherein the endpiece is secured to the rod by screwing the threaded section on the distal end of the rod into the tapped section of the rigid part of the endpiece.

21. (Previously Presented) The method of claim 14 wherein the tool includes a knob fixed to a proximal end of the tool.

22. (Previously Presented) The method of claim 21 wherein the second force is an impaction force applied to the knob fixed to the proximal end of the tool.

23. (Canceled)

24. (Currently Amended) A method of positioning a prosthetic acetabulum with inner and outer surfaces in an anatomical or prosthetic cavity of a patient's hip, comprising the steps of:

(a) contacting the prosthetic acetabulum with a tool having a head movably mounted on a rod adapted to engage an endpiece removably secured to the rod, wherein the endpiece includes a plurality of petals in an elastically deformable ring, wherein the petals have ~~having an inner surfaces face~~ adapted to contact the head and ~~an outer surfaces~~ adapted to contact an inner surface of the prosthetic acetabulum;

(b) forcing the head into engagement with the inner surfaces of the petals in deformable ring to radially wedge the outer surfaces of the petals of the deformable ring against the inner surface of the prosthetic acetabulum to secure the prosthetic acetabulum to the tool;

(c) positioning the ~~an~~ outer surface of the prosthetic acetabulum in a cavity in a patient's hip;

(d) applying a force to the tool to seat the prosthetic acetabulum in the cavity;

(e) releasing the head from engagement with the petals of the deformable ring to allow the deformable ring to unsecure the prosthetic acetabulum from the tool; and

(f) withdrawing the tool from the positioned prosthetic acetabulum.

25. (Previously Presented) The method of claim 24 further comprising the step of selecting the endpiece from a plurality of endpieces, wherein the selected endpiece closely matches the size of the inner surfaces of the prosthetic acetabulum.

26. (Currently Amended) The method of claim 25 further comprising the step of securing the selected endpiece to the rod by screwing a threaded section on the distal end of the rod into a tapped section in a rigid part of the endpiece.

27. (Previously Presented) The method of claim 24, wherein the step of forcing the head into engagement with the inner surfaces of the petals of the deformable ring includes rotating a grip screwed on a threaded section of the rod in a first direction to urge a movable sleeve fitted between the grip and the head toward a distal position on the rod.

28. (Previously Presented) The method of claim 24 wherein the step of withdrawing the tool from the positioned prosthetic acetabulum includes rotating a grip screwed on a threaded section of the rod in a second direction to urge a movable sleeve fitted between the grip and the head toward a proximal position on the rod.

29. (Previously Presented) The method of claim 24 wherein the step of applying a force to the tool to seat the prosthetic acetabulum includes applying an impaction force to a knob fixed to a proximal end of the tool.

30. (Canceled)

31. (Currently Amended) A method of positioning a prosthetic acetabulum with inner and outer surfaces in an anatomical or prosthetic cavity of a patient's hip, comprising the steps of:

(a) providing a tool having a handle that includes a rod having a threaded medial portion and a threaded distal portion, a movable sleeve adapted to move in distal and proximal directions on the rod, a grip adapted to rotate on the threaded medial portion of the rod to move the sleeve, a movable head adapted to move in distal and proximal direction on the rod and to engage ~~an inner surface of~~ an endpiece, and an endpiece having an elastically deformable ring including a plurality of petals mounted on a rigid part that contains a

threaded portion to secure the endpiece to the rod, wherein the petals have an outer surfaces  
~~of the deformable ring~~ is adapted to engage the an inner surface of a prosthetic acetabulum  
when the head is forced on ~~an inner surfaces~~ of the ~~petals~~deformable ring[,];

- (b) placing the endpiece of the tool into the prosthetic acetabulum[,];
- (c) forcing the head into the inner surfaces of the petals ~~of the deformable ring~~ by  
rotating the grip in a first direction to radially expand the ~~petals~~deformable ring to an  
expanded configuration and secure the endpiece in the prosthetic acetabulum by gripping the  
inner surface of the prosthetic acetabulum with the outer surfaces of the petals ~~deformable~~  
~~ring~~[,];
- (d) positioning the prosthetic acetabulum in a cavity of a patient's hip[,];
- (e) applying an impaction force to the tool to seat the prosthetic acetabulum in the  
cavity[,];
- (f) disengaging the head from the inner surface of the ~~petals~~deformable ring by  
rotating the grip in a second direction to allow the ~~petals~~deformable ring to recover to a non-  
expanded configuration[,]; and
- (g) withdrawing the tool from the prosthetic acetabulum.

32. (Previously Presented) The method of claim 31 further comprising the step of selecting  
the endpiece from a plurality of endpieces, wherein the selected endpiece closely matches the  
size of the inner surface of the prosthetic acetabulum.

Please add new claims 33 and 34.

33. (New) The method of claim 18 wherein the petals are connected to the rigid part of  
the endpiece by elastically deformable connecting zones.

34. (New) The method of claim 33 wherein the petals move apart radially in a  
homogenous manner.

35. (New) The method of claim 33 wherein the petals move radially in order to contact  
the inner surface of the acetabulum.